**Tripp Lite**
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

# Model #: BP240V1407C-1PH

## External battery pack for use with select Tripp Lite UPS Systems

### Highlights

- Extends runtime of compatible Tripp Lite UPS Systems using 240VDC configuration
- Includes built in 7A charger
- Includes UPS connection cabling
- 10 year design life
- 1-year warranty

### Description

Tripp Lite's BP240V1407C-1PH External Battery Pack with built-in 7A charger offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes heavy gauge cabling to connect to host UPS. Multiple BP240V1407C-1PH batteries can be daisy-chained for longer runtime configurations with appropriate contractor-supplied battery pack interconnection cabling (see manual). Internal battery charger is powered via hardwire connection to 120V 30A electrical service.

COMPATIBLE UPS SYSTEMS: SU5000RT3U, SU5000RT3UHV, SU6000RT3U, SU6000RT3UHV, SU8000RT3U, SU8000RT3U1TF, SU10KRT3U, SU10KRT3UHV, SU10000RT3U, SU10000RT3U2TF and other Tripp Lite UPS systems specifying the use of this battery pack

### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- Cabling to connect one BP240V1407C-1PH is included - cabling for additional battery packs is contractor supplied
- Includes built-in 7A charger powered via hardwire 120VAC 30A input connection
- 1 year warranty

### Specifications

| | |
|---|---|
| **BATTERY** | |
| **Expandable battery runtime** | Multiple battery packs can be daisy-chained to the UPS for extended runtime. Configuration specific cabling for multi-battery pack configurations is contractor provided. |
| **Connects to UPS via** | Included cabling enables connection between unique UPS connector and hardwire DC terminals in battery pack. Cabling to connect multiple external battery packs is contractor provided. |
| **DC system voltage** | 240VDC |
| **PHYSICAL** | |
| **Shipping weight (lbs)** | 2555 |
| **Shipping weight (kg)** | 1160 |
| **Shipping Dimensions (HWD/in)** | 63 x 37 x 36 |
| **Shipping Dimensions (HWD/cm)** | 160 x 94 x 91.4 |

| | |
|---|---|
| **Unit weight (lbs)** | 2463 |
| **Unit weight (kg)** | 1118.2 |
| **Unit Dimensions (HWD/in)** | 60 x 32.4 x 28.8 |
| **Unit Dimensions (HWD/cm)** | 152.4 x 82.3 x 73.2 |
| **Material of construction** | Steel |
| **Form factors supported** | Tower |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4067.

©2009 Tripp Lite.  All Rights Reserved.